

M8 female straight shielded wireable screw term. 3-pol. 0,14x0,5mm²

Female straight
3-pole, shielded
Screw terminals
Connection diameter: 0.14...0.5 mm²

Image

Vicarious picture

Approvals**Form**

08661

Technical Data



Operating voltage	max. 60 V AC/DC
Operating current per contact (40 °C)	max. 4 A
Connection diameter	0.14... 0.5 mm ²
Clamping range (cable diameter)	3.5...5.5 mm
Protection	IP65 and IP67 when plugged and screwed down (EN 60529)
Temperature range	-25...+85 °C

Commercial data

Net weight	52
Net weight	52
Weight unit	gram
Basic unit	pc.
Customs tariff number	85369010
Unit (piece)	1
Limited value	1

All data on this data sheet was compiled carefully.

Liability regarding correctness, completeness, and actuality is limited to gross negligence. Created: 06/12

Circuit diagram**Dimension drawing**

Representante oficial de:



[Argentina – Uruguay – Paraguay – Bolivia – Colombia – y Perú.]



Calle 49 N° 5764 - Villa Ballester (B1653AOX) - Prov. de Buenos Aires - ARGENTINA
Tel: (+54 11) 4768-4242 / Fax: (+54 11) 4849-1212
Mail: ventas@nakase.com.ar / Web: www.nakase.com.ar

