

**CAN system cable connector Termination, (120 Ohm) up to 1Mbits/s**

Bus connection plug  
 SUB-D9 (female)  
 Screw terminals  
 to 1 Mbit/s with switchable terminal resistors  
 CANopen

**Image**

Vicarious picture

**Technical Data**

Terminator	integrated, switchable
Transfer rate	to 1 Mbit/s with switchable terminal resistors

**General data**

Protection	IP20
Temperature range	0...+60 °C (storage temperature -25...+80 °C)
Dimensions H x W x D	65 x 48 x 16 mm

**Commercial data**

Net weight	46
Net weight	46
Weight unit	gram
Basic unit	pc.
Customs tariff number	85369010
Unit (piece)	1
Limited value	1

**Comments**

Plastic housings with good resistance against chemicals and oils.  
 The resistance to aggressive media should be individually tested for your application. Further details on request.

Representante oficial de:



[Argentina – Uruguay – Paraguay – Bolivia – Colombia – y Perú.]



Calle 49 N° 5764 - Villa Ballester (B1653AOX) - Prov. de Buenos Aires - ARGENTINA  
Tel: (+54 11) 4768-4242 / Fax: (+54 11) 4849-1212  
Mail: [ventas@nakase.com.ar](mailto:ventas@nakase.com.ar) / Web: [www.nakase.com.ar](http://www.nakase.com.ar)

