

PROFIBUS plug-male, cut clamp, 180° flex

Bus Connection Plug 180°
SUB-D9 (male)
Cut clamps
PROFIBUS (flexible cable)

Image

Vicarious picture

Approvals**Technical Data**

Terminator	integrated, switchable
Operating voltage	via the fieldbus device; 4.75...5.25 V DC
Transfer rate	to 12 Mbit/s
Connection	PROFIBUS, flexible FC cable, 1 × 2 × 0.64 mm, stranded, for outer diameter 8.0 ± 0.5 mm

General data

Protection	IP20
Housing	Plastic, metallized, shielded
Temperature range	0...+60 °C (storage temperature -25...+80 °C)
Dimensions H × W × D	72 x 35 x 17 mm

Commercial data

Net weight	33
Net weight	33
Weight unit	gram
Basic unit	pc.
Customs tariff number	85369010
Unit (piece)	1
Limited value	1

All data on this data sheet was compiled carefully.

Liability regarding correctness, completeness, and actuality is limited to gross negligence. Created: 06/12

Representante oficial de:



[Argentina – Uruguay – Paraguay – Bolivia – Colombia – y Perú.]



Calle 49 N° 5764 - Villa Ballester (B1653AOX) - Prov. de Buenos Aires - ARGENTINA
Tel: (+54 11) 4768-4242 / Fax: (+54 11) 4849-1212
Mail: ventas@nakase.com.ar / Web: www.nakase.com.ar

