


PROFIBUS plug-male, cut clamp, 180 rigid

Bus Connection Plug 180°
SUB-D9 (male)
Cut clamps
PROFIBUS (rigid cable)

Image

Vicarious picture

Approvals**Technical Data**

| | |
|-------------------|--|
| Terminator | integrated, switchable |
| Operating voltage | via the fieldbus device; 4.75...5.25 V DC |
| Transfer rate | to 12 Mbit/s |
| Connection | PROFIBUS, FC-cable rigid, 1 × 2 × 0.64 mm, for outer diameter 8.0 ± 0.5 mm |

General data

| | |
|----------------------|---|
| Protection | IP20 |
| Housing | Plastic, metallized, shielded |
| Temperature range | 0...+60 °C (storage temperature -25...+80 °C) |
| Dimensions H × W × D | 72 x 35 x 17 mm |

Commercial data

| | |
|-----------------------|----------|
| Net weight | 33 |
| Net weight | 33 |
| Weight unit | gram |
| Basic unit | pc. |
| Customs tariff number | 85369010 |
| Unit (piece) | 1 |
| Limited value | 1 |

All data on this data sheet was compiled carefully.

Liability regarding correctness, completeness, and actuality is limited to gross negligence. Created: 06/12

Representante oficial de:



[Argentina – Uruguay – Paraguay – Bolivia – Colombia – y Perú.]



Calle 49 N° 5764 - Villa Ballester (B1653AOX) - Prov. de Buenos Aires - ARGENTINA
Tel: (+54 11) 4768-4242 / Fax: (+54 11) 4849-1212
Mail: ventas@nakase.com.ar / Web: www.nakase.com.ar

