


**PROFIBUS plug-male (Sub-D), cut clamp for rigid cables**

Bus connection plug  
 SUB-D9 (male)  
 Cut clamps  
 PROFIBUS (rigid cable)

**Image**

Vicarious picture

**Approvals****Technical Data**

Terminator	integrated, switchable
Operating voltage	via the fieldbus device; 4.75...5.25 V DC
Transfer rate	to 12 Mbit/s
Connection	PROFIBUS, FC-cable rigid, 1 × 2 × 0.64 mm, for outer diameter 8.0 ± 0.5 mm

**General data**

Protection	IP20
Housing	Plastic, metallized, shielded
Temperature range	0...+60 °C (storage temperature -25...+80 °C)
Dimensions H × W × D	72 x 40 x 17 mm

**Commercial data**

Net weight	39
Net weight	39
Weight unit	gram
Basic unit	pc.
Customs tariff number	85369010
Unit (piece)	1
Limited value	1

All data on this data sheet was compiled carefully.

Liability regarding correctness, completeness, and actuality is limited to gross negligence. Created: 06/12

Representante oficial de:



[Argentina – Uruguay – Paraguay – Bolivia – Colombia – y Perú.]



Calle 49 N° 5764 - Villa Ballester (B1653AOX) - Prov. de Buenos Aires - ARGENTINA  
Tel: (+54 11) 4768-4242 / Fax: (+54 11) 4849-1212  
Mail: [ventas@nakase.com.ar](mailto:ventas@nakase.com.ar) / Web: [www.nakase.com.ar](http://www.nakase.com.ar)

