

SVS valve form A 18mm field-wireable Replaced Art.-No. 3129822

Form A (18 mm)
110 V AC/DC with LED and VDR
PG 9

Image



Vicarious picture

Approvals



Form

29101

Technical Data

Operating voltage	110 V AC/DC $\pm 10\%$
Operating current per contact (40 °C)	max. 4 A
Clamping range (cable diameter)	6...8 mm
Hold-on	max. 100 W(VA)
Compression gland	PG 9; (PG11 and NPT 1/2" on request)
Terminals	4 mm ² single core, with ferrule end 1.5 mm ²
Protection	IP65 when plugged and screwed down (EN 60529), with gland
Temperature range	-20...+60 °C

Commercial data

Net weight	32
Net weight	32
Weight unit	gram
Basic unit	pc.
Customs tariff number	85369010
Unit (piece)	1
Limited value	1


Comments

Plastic housings with good resistance against chemicals and oils.
The resistance to aggressive media should be individually tested for your application. Further details on request.


All data on this data sheet was compiled carefully.

Liability regarding correctness, completeness, and actuality is limited to gross negligence. Created: 06/12


Contact layout



Circuit diagram



Dimension drawing



Height: 41 mm

Representante oficial de:



[Argentina – Uruguay – Paraguay – Bolivia – Colombia – y Perú.]



Calle 49 N° 5764 - Villa Ballester (B1653AOX) - Prov. de Buenos Aires - ARGENTINA
Tel: (+54 11) 4768-4242 / Fax: (+54 11) 4849-1212
Mail: ventas@nakase.com.ar / Web: www.nakase.com.ar

