

A close-up photograph of a cylindrical metal component, likely a sensor or actuator, with a black cable attached. The component has a silver-colored metal body with a red ring around the central opening. The cable is black and extends from the side of the component.

-
- A close-up photograph of a cylindrical metal component, likely a sensor or actuator, with a black cable extending from it. The component has a silver-colored metal body with a red ring around the central opening. The background is white.



A close-up photograph of a cylindrical metal component, likely a sensor or actuator, with a black cable extending from it. The component has a silver-colored metal body with a red ring around the central opening. The background is white.



A close-up photograph of a cylindrical metal component, likely a sensor or actuator, with a black cable attached. The component has a silver-colored metal body with a red ring around the central opening. The cable is black and extends from the side of the component.

A close-up photograph of a cylindrical metal component, likely a sensor or actuator, with a black cable extending from it. The component has a silver-colored metal body with a red ring around the central opening. The background is white.

A close-up photograph of a cylindrical metal component, likely a sensor or actuator, with a black cable extending from it. The component has a silver-colored metal body with a red ring around the central opening. The background is white.

	Incremental									
	ROD 1020			ROD 1030			ROD 1080		ROD 1070	
Incremental signals	 TTL			 HTLs			 1 V _{PP} ¹⁾		 TTL	
Line counts*	100 1000	200 1024	250 1250	360 1500	400 2000	500 2048	720 2500	900 3600	1000 2500 3600	
Reference mark	One									
Integrated interpolation*	–							5-fold		10-fold
Cutoff frequency –3 dB	–			–			≥ 180 kHz		–	
Scanning frequency	≤ 300 kHz			≤ 160 kHz			–		≤ 100 kHz	
Edge separation a	≥ 0.39 μs			≥ 0.76 μs			–		≥ 0.47 μs	
System accuracy	1/20 of grating period									
Power supply	5 V DC ± 10 %			10 to 30 V DC			5 V DC ± 10 %		5 V DC ± 5 %	
Current consumption without load	≤ 120 mA			≤ 150 mA			≤ 120 mA		≤ 155 mA	
Electrical connection	Cable 1 m /5 m, with or without coupling M23							Cable 5 m without M23 coupling		
Shaft	Solid shaft D = 4 mm									
Mech. perm. speed n	≤ 12 000 min ^{–1}									
Starting torque	≤ 0.001 Nm (at 20 °C)									
Moment of inertia of rotor	≤ 0.5 · 10 ^{–6} kgm ²									
Shaft load	Axial: 5 N Radial: 10 N at shaft end									
Vibration 55 Hz to 2000 Hz	≤ 100 m/s ² (EN 60068-2-6)									
Shock 6 ms	≤ 1 000 m/s ² (EN 60068-2-27)									
Max. operating temp. ²⁾	100 °C			70 °C			100 °C		70 °C	
Min. operating temp.	For fixed cable: –30 °C Moving cable: –10 °C									
Protection EN 60529	IP 64									
Weight	Approx. 0.09 kg									

Bold: These preferred versions are available on short notice

* Please select when ordering

¹⁾ Restricted tolerances: Signal amplitude 0.8 to 1.2 V_{PP}

²⁾ For the correlation between the operating temperature and the shaft speed or supply voltage, see *General Mechanical Information*

	Absolute	
	Singleturn	
	ROC 1023	ROC 1013
Absolute position values	EnDat 2.2	
Ordering designation	EnDat 22	EnDat 01
Positions per revolution	8388608 (23 bits)	8192 (13 bits)
Revolutions	–	
Code	Pure binary	
Elec. permissible speed Deviations ¹⁾	12000 min ⁻¹ (for continuous position value)	4000 min ⁻¹ /12000 min ⁻¹ ± 1 LSB/± 16 LSB
Calculation time t _{cal}	≤ 7 µs	≤ 9 µs
Incremental signals	–	~ 1 V _{PP} ²⁾
Line count	–	512
Cutoff frequency –3 dB	–	≥ 190 kHz
System accuracy	± 60"	
Power supply	3.6 V to 14 V DC	
Power consumption (maximum)	3.6 V: ≤ 600 mW 14 V: ≤ 700 mW	
Current consumption (typical; without load)	5 V: 85 mA	
Electrical connection	Cable 1 m, with M12 coupling	Cable 1 m, with M23 coupling
Shaft	Stub shaft Ø 4 mm	
Mech. perm. speed n	12000 min ⁻¹	
Starting torque	≤ 0.001 Nm (at 20 °C)	
Moment of inertia of rotor	Approx. 0.5 · 10 ⁻⁶ kgm ²	
Shaft load	Axial: 5 N Radial: 10 N at shaft end	
Vibration 55 Hz to 2000 Hz Shock 6 ms	≤ 100 m/s ² (EN 60068-2-6) ≤ 1000 m/s ² (EN 60068-2-27)	
Max. operating temp.	100 °C	
Min. operating temp.	For fixed cable: –30 °C Moving cable: –10 °C	
Protection EN 60529	IP 64	
Weight	Approx. 0.09 kg	

¹⁾ Velocity-dependent deviations between the absolute and incremental signals

²⁾ Restricted tolerances: Signal amplitude 0.80 to 1.2 V_{PP}

[illegible]

Representante oficial de:



HEIDENHAIN

[Argentina – Bolivia – Chile – Colombia - Costa Rica – Ecuador - El Salvador –
Guatemala – Honduras – Nicaragua – Panamá – Paraguay – Perú -
República Dominicana – Uruguay – Venezuela.]



Calle 49 N° 5764 - Villa Ballester (B1653AOX) - Prov. de Buenos Aires - ARGENTINA
Tel: (+54 11) 4768-4242 / Fax: (+54 11) 4849-1212
Mail: ventas@nakase.com.ar / Web: www.nakase.com.ar

